

LGM
PRODUCTS
 +44 1252 725257
 sales@lgmproducts.com



SIGNALINE
 Linear detection solution Product Brochure





About Us

Signaline is a comprehensive range of linear detection systems providing solutions for fire and water leak detection.

Our linear detectors are 100% manufactured in the UK and have a wide range of third party approvals from both international organisations and local bodies, testifying to the high quality of the products.

Our detectors are sold in 50m increments, sized to suit the needs of each individual customer.

Certification

LGM Products is proud to be a market leader in customer service. Our third party approved quality assurance systems gives our customers the confidence they need in a reliable and active supplier.

Check our website to download a copy of our ISO9001:2015 quality assurance certificate.

Signaline also carries VdS Approval for the Signaline HD SKM-03 and Signaline HD SKM-95 analogue linear heat detection.

Signaline FT cable is UL and FM approved.





Signaline Project List

| Project | Product | Customer | Country |
|---------------------------------|-----------------------|--------------------------|-------------|
| Floating roof tank | Signaline FT-105-R | PTT PLC | Australia |
| Silicon conveyor | Signaline FT-105-R | Simcoa | Australia |
| Meat Smoker rooms | Signaline FT-68 | Hochreiter Fleischwaren | Austria |
| Mongola Power station | Signaline FT-88-R | Petromax Refinery LTD. | Bangladesh |
| Ülemiste Junction Road Tunnel, | Signaline FT-68 | Ulemiste CC | Estonia |
| Farm Building Protection | Signaline FT-68 | Undisclosed | Estonia |
| Data Server Centre | Signaline HD | Google | Finland |
| BMW Parkhaus, Germany | Signaline HD | BMW Group | Germany |
| Sixt Garden Office Pullach | Signaline HD | Sixt AG | Germany |
| Residence Car Park | Signaline HD | Wohnanlage mit TG | Germany |
| Schwabing Premier Parking | Signaline HD | Wohnanlage mit TG | Germany |
| Nora Gas Tank Farm, Ireland | Signaline FT-68-R | Balfour Beatty | Ireland |
| Luxembourg Int. Airport | Signaline HD | Tief Garage Parkhaus | Luxembourg |
| Extinguishing CAF | Signaline FT-88-R | BlusDirect | Netherlands |
| Livestock Stables | Signaline FT-68 | Undisclosed | Netherlands |
| Floating Roof Tank | Signaline FT-105-R | Undisclosed | Netherlands |
| Mogas Tank, Qatar | Signaline FT-105 | Qatar Petroleum | Qatar |
| Poze Magazii Port | Signaline FT-88-R | S.C TRN Sig Expert S.R.L | Romania |
| Electric substations | Signaline FT-88 | Petrom OMV | Romania |
| Pancevo Refinery Tank Farm | Signaline FT-105-R | Siemens D.o.o | Serbia |
| US Army Barracks, Singapore | Signaline FT | US Army | Singapore |
| Wooden Building Protection | Signaline FT68 & FT88 | Undisclosed | Sweden |
| Criminal Record Facility | Signaline FT-68 | Criminal Records Bureau | Dubai, UAE |
| Trafalgar Road Car Park | Signaline FT-68 | Brighton City Council | UK |
| Millennium Square Car Park | Signaline HD | Bristol City Council | UK |
| Cottam Hill Power Station | Signaline FT-68 | EDF Energy | UK |
| Hackney London Borough Carparks | Signaline HD | Hackney Borough Council | UK |
| Paper mill | Signaline FT-88 | Ironmountain | UK |
| Heathrow Terminal 3 | Signaline HD | Kone PLC. | UK |
| Heathrow Terminal 5 | Signaline HD-S | Kone PLC. | UK |
| SHS Security | Signaline FT-88-R | Octagon LTD. | UK |

Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com


Web: signaline.com

ISO 9001:2015 certified


Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom



SIGNALINE HEAT



A versatile heat detection solution with large coverage and a small profile. Signaline HEAT carries international approvals and is ideal for various industrial and commercial buildings.



Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom



Signaline HD

WHAT IS HD?

Signaline HD is an analogue resettable linear heat detector that monitors significant increases in temperature.

An electronic controller connected to the cable monitors the condition of the cable to sense any change in temperature by continually measuring the electrical resistance between the metallic core and screen. If the change in temperature is sufficient the controller creates an alarm.

KEY POINTS

- EN54-5 approved
- Sold in 50m increments, up to 500m per reel
- Zero maintenance
- Weather-proof heat detector
- Fully resettable
- Addressable and conventional controllers available
- No setup or programming required
- Intrinsically safe when integrated with a barrier
- Up to 300m in a single zone



Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom




Signaline HD

ANALOGUE HEAT DETECTION

Signaline HD

- PVC outer coat
- Reports fire upon a change in resistance
- Provides class C response (EN54 approved)
- Resettable once cool. No need to replace unless damaged



Signaline HD-R

- Signaline HD with protective nylon coating
- Resistant to oils, corrosive chemicals/gasses and high UV levels
- Provides class C response (EN54 approved)
- Resettable once cool. No need to replace unless damaged



Signaline HD-S

- Signaline HD with a braided stainless steel sleeve
- High mechanical protection
- Helps prevent expensive maintenance/repair costs
- Resettable once cool. No need to replace unless damaged





Signaline HD CONTROLLERS

All Signaline HD Linear Heat Detectors (Signaline HD) must be used with a controller.

Signaline HD Controllers provide early warning of an impending fire by detecting overheating in cable ducts, road tunnels, escalators, car parks, lift shafts, conveyer belts and similar difficult to monitor environments.

The system uses Signaline HD Linear Heat Detector and a Signaline HD Controller plus a Signaline End of Line Unit. Signaline HD Controllers are very simple and easy to use.

All Signaline controllers are delivered complete with End of Line.



HD-SKM-03

- Conventional controller
- The SKM measures the condition of the cable. (normal, open circuit, short circuit, fire)
- Equipped with volt free fire & fault relays that are connected to the fire control panel

HD-SKM-95

- Addressable loop-powered controller
- The SKM measures the condition of the cable. (normal, open circuit, short circuit, fire)

- IP65 rated
- EN54 part 5, class-C approved
- Monitors up to 300m of cable
- Economical and simple to operate



Signaline HD

ACCESSORIES

EOL

- Standard End of Line device for use with Signaline HD
- Included with purchase of Signaline controllers
- IP66 enclosure



UCB

- Can be used as an end of line enclosure, junction box or an interposing line unit
- Supplied with appropriately sized cable glands, terminal block and 470, 680 ohm resistors
- IP66 enclosure



K Clip

- Designed specifically for Signaline HD
- No wall plug or screw needed
- 6mm dia. knock-in spigot
- Cable stands off wall by 4.5mm
- More clips available on pages 12-13





Signaline FT


WHAT IS FT?

Signaline Fixed Temperature Linear Heat Detector (Signaline FT) detects a build up of heat anywhere along its length. When any point along the length of the cable reaches a predetermined temperature an alarm is initiated.

Signaline FT is available in four different temperature settings and two outer cover options making the Signaline FT suitable for use in a very wide range of applications.

KEY POINTS

- UL, cUL and FM Approved
- PVC or nylon outer coating as standard
- Four alarm temperatures to choose from
- Easy to install
- Large zone lengths
- Range includes optional alarm locator
- Maintenance free
- No false alarms



Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom




Signaline FT

FIXED TEMPERATURE CABLE

Signaline FT-68

- 68°C pre-set alarm temperature
- cUL, UL and FM approved
- PVC coat
- Simple installation & cost-effective



Signaline FT-68-R

- 68°C pre-set alarm temperature
- cUL and UL approved
- Resistant to oils, corrosive chemicals/gasses and high UV levels
- Nylon outer sheath



Signaline FT-88

- 88°C pre-set alarm temperature
- cUL, UL and FM approved
- PVC coat
- Simple installation & cost-effective






Signaline FT

FIXED TEMPERATURE CABLE

Signaline FT-88-R

- 88°C pre-set alarm temperature
- cUL, UL and FM approved
- Resistant to oils, corrosive chemicals/gasses and high UV levels
- Nylon outer sheath



Signaline FT-105

- 105°C pre-set alarm temperature
- cUL, UL and FM approved
- White PVC outer sheath



Signaline FT-105-R

- 105°C pre-set alarm temperature
- cUL and UL approved
- Resistant to oils, corrosive chemicals/gasses and high UV levels
- Nylon outer sheath





Signaline FT

FIXED TEMPERATURE CABLE

Signaline FT-185-R

- 185°C pre-set alarm temperature
- cUL and UL approved
- Resistant to oils, corrosive chemicals/gasses and high UV levels
- Designed to withstand very high ambient temperatures



Signaline FT-230-X

- 230°C pre-set alarm temperature
- UL approved
- Resistant to oils, corrosive chemicals/gasses and high UV levels
- Can withstand an ambient temperature of 180°C





Signaline FT ACCESSORIES

Signaline LocatorPlus

The Signaline LocatorPlus is a dual zone module for monitoring up to two zones of Signaline FT or FT-R Digital Linear Heat Detection Cable. If an overheat/fire situation triggers either zone of the cable, this unit automatically calculates and displays the distance along the cable, in feet and metres, to the alarm point.

The two zones can operate independently of each other, or in interlocking mode. A separate alarm and normally conducting fault output are provided for each zone. Signaline LocatorPlus will operate with any conventional or addressable fire alarm control panel.



- IP65 rated
- UL certified
- Suitable for all FT cable
- Backlit LCD display
- Two zones of Signaline FT or FT-R cable
- Detects alarm point from 100 to 3000 meters per zone
- Independent or Interlocking mode
- RS-485 MODBUS RTU output
- Power, Fault and Alarm LED indication
- Integrated alarm buzzer

Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom



Signaline Heat

ACCESSORIES

NOTE: For UK installations, plastic clips (A/T/K) may not be placed on walls or the underside of ceilings in escape routes (Amendment 3, BS 7671: 2008. 17th Edition)

T Clip

- Polypropylene plastic moulding with slot for cable
- Can be combined with a tie wrap to secure cable to the clip
- Can be fixed to surface with screw or percussion pin
- Sold as clip only. Fixing screw and tie wrap not included



A Clip

- Nylon clip with M6 fixing holes
- Ideal where heat transfer from the fixing point to the cable must be minimized



P Clip

- Made of stainless steel
- Highly resistant to oils and greases
- Wide temperature tolerance
- UV and ozone resistant cushion insulator





Signaline Heat

ACCESSORIES


Edge Clip

- Designed to attach to steelwork with 3-8mm thickness. Other thicknesses available if required
- Made of steel with a zinc finish
- Cable attaches to clip with the supplied neoprene sleeve and cable tie



J Clip

- Designed to attach to steelwork with 4-6.8mm thickness
- Made of steel with a zinc finish
- Cable attaches to clip with the supplied neoprene sleeve and cable tie





Signaline Heat

ACCESSORIES

Signaline Retractable Cable

- A multi-core extending cable. Oil, grease and chemical resistant
- Perfect for floating roof petro-chem storage tanks
- Designed to connect Signaline cable fitted to the circumference of a tank with an EOL device at the roof of the tank
- Low cost solution made to direct specification



Auto Cable Collector

- Turnbuckle with 24m extending retractable cable
- Designed to connect Signaline cable fitted to the circumference of a tank with an EOL device at the roof of the tank
- Fitted Ex junction box



UCB

- Can be used as an end of line enclosure, junction box or an interposing line unit
- Supplied with appropriately sized cable glands, terminal block, 470 and 680 ohm resistors
- IP66 enclosure





Signaline Heat ACCESSORIES

Signaline EX UCB

- Can be used as an ATEX approved end of line enclosure, junction box or interposing line unit
- Supplied with cable glands, terminal block and 470 & 680 ohm resistors.
- Can interconnect, terminate and join lengths of any Signaline cable



MTL 5561

- Loop-powered 2-channel interface for use with conventional fire and smoke detectors located in hazardous areas
- ATEX approved
- Reverse input polarity protection
- "No-fail" earth fault protection



Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom



SIGNALINE



Signaline WATER detection cable can be used to protect critical applications where equipment might be vulnerable to water ingress. Early detection of water can reduce or prevent costly downtime.



Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom



Signaline Water

WHAT IS WD?


Signaline WATER detection cable can be used to protect critical applications where equipment might be vulnerable to water ingress. It can be installed with up to 1km of cable per module.

The flexible but tough detection cable acts as a sensor along its entire length. Contact with water causes a short-circuit and sends the panel into alarm.

Applications include data centres, server rooms, document stores and machinery.

KEY POINTS

- 3.75, 7.5, 15, 30 and 100m lengths available
- Unique 4-core twisted cable (2x monitoring, 2x water sensitive)
- Protective nylon fishnet braid allows the sensing cable to remain protected while exposed to potential water
- The monitor can connect to a panel, BMS or other management system
- No programming required
- Plug and play setup
- Made in the UK



Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom



Signaline Water WATER SENSING CABLE

Signaline WD

- Water detection cable
- Unique 4-core twisted cable with a nylon fishnet braid
- Available in 3.75m, 7.5m, 15m, 30m & 100m lengths
- Pre-fitted connectors and hard wearing cable



Signaline WDM-KM

- Monitors water detection cable
- Allows for termination of power, alarm and fault connections
- Completely sealed. Protected from water damage



Signaline Water Detection Control Panel

- Provides a fully monitored detection solution
- 2 and 4 zone versions available
- One-man walk test mode
- 2x monitored sounder circuits



Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom



Signaline Water ACCESSORIES

WIB Interposing Box

- Interfaces the Signaline WDM-KM with a water control panel
- One WIB is required per zone
- Compatible with Apollo XP95 and Hochiki ESP systems
- IP66 rated enclosure



Water Lead-in Cable

- Allows for a panel to be placed away from the detection zone
- Fitted with connectors to allow for instant tool-free installation



Nylon P Clip

- Made of flame-retardant nylon 66
- Resistant to chemical corrosion and UV light
- Small profile
- Low heat transfer





VISIT US AT SIGNALINE.COM

SIGNALINE by LGM Products
+44 1252 725257
sales@lgmproducts.com [Contact us](#)

[Linear Heat Detection](#) [Linear Water Detection](#) [Tech info](#) [Approvals](#) [News](#) [About us](#)

Linear heat detection and linear water detection systems, made in the UK and trusted by businesses in 49 countries around the world. [Download our brochure \(PDF\)](#)

Linear Heat Detection
Analogue and fixed temperature linear heat detection cables for use in addressable and conventional fire alarm systems

Linear Water Detection
Linear water detection cable to protect critical equipment vulnerable to water ingress

[Download our brochure \(PDF\)](#)

News and articles
Success at the Securex Exhibition in Poland
Between 23-26th April 2018 LGM Products was pleased to present our range of Signaline Linear heat detection cables at the Securex Exhibition in Poznan in Poland. This was the 22nd Edition of the exhibition held at the Poznan International Fair...
See you at The Parking & Property Show!
LGM Products is pleased to announce that we will be exhibiting our range of Signaline linear heat detection at the Parking & Property Show in London on the 10th May 2018. The annual Parking & Property event is the one day in...

Tweets by @Signaline
Signaline (@Signaline) Huge congratulations to the team for padding 13km of the Thames for @Carers4Costley! Couldn't be done without the fantastic support from Sue and Sue (@royalcanoeclub) Thanks for all the support - we have raised £3,395 so far! justgiving.com/fundraising/g...
[Embed](#) [View on Twitter](#)

LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom
+44 1252 725257 sales@lgmproducts.com
Website copyright © LGM Products, designed and built by Tim Wakeling Hosted on a UK server
Terms of use Cookies Privacy policy

The home of our award winning linear heat detection solution

Complete Signaline catalogue, datasheets, guides & product support

General sales: sales@lgmproducts.com

Technical support: technical@lgmproducts.com

Accounts: accounts@lgmproducts.com

Phone: +44(0)1252 725257

Company registration no.: 3574049

VAT No.: GB709 1120 69

Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: signaline.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom



Tel: +44(0)1252 725257

Fax: +44(0)1252 727627

©2018/19 LGM Products Ltd.

Email: sales@lgmproducts.com

Web: www.lgmproducts.com

ISO 9001:2015 certified

Address: LGM Products Ltd, Unit 15 Riverside Industrial Park, Farnham, Surrey, GU9 7UG, United Kingdom.